

## COMPRESORES HERMÉTICOS

**COMPRESORES ALTA TEMPERATURA Tríf. 400 V. 50 Hz. R-134a, R-404A/R-507, R-407C**

Código	Modelo	HP	Cilindrada cm <sup>3</sup>	Int. A.	Tipo GAS	Rendimiento W.				€
						+ 5°C	0°C	-5°C	-10°C	
CO3600	MTZ18-4	1 1/2	30,23	5	R-134a	2.250	1.720	1.270	890	671,36
					R-404A	3.670	2.880	2.220	1.670	
					R-407C	3.420	2.620	1.930		
CO3601	MTZ22-4	1 3/4	38,12	6	R-134a	2.960	2.250	1.670	1.190	780,60
					R-404A	4.970	3.900	3.000	2.260	
					R-407C	4.500	3.510	2.660		
CO3602	MTZ28-4	2	48,06	7,5	R-134a	3.720	2.830	2.130	1.570	840,38
					R-404A	6.420	5.090	3.960	3.000	
					R-407C	5.840	4.520	3.390		
CO3603	MTZ32-4	2 1/4	53,86	8	R-134a	4.370	3.320	2.470	1.790	909,64
					R-404A	7.250	5.790	4.540	3.490	
					R-407C	6.600	5.210	4.000		
CO3604	MTZ36-4	3	60,47	9	R-134a	5.380	4.250	3.300	2.510	974,81
					R-404A	8.290	6.710	5.340	4.170	
					R-407C	7.510	6.020	4.700		
CO3605	MTZ40-4	3 1/2	67,89	10	R-134a	5.810	4.720	3.770	2.960	1.088,03
					R-404A	9.280	7.560	6.080	4.810	
					R-407C	8.710	7.020	5.530		
CO3607	MTZ50-4	4	85,64	12	R-134a	7.140	5.470	4.100	2.990	1.215,94
					R-404A	11.340	8.930	6.930	5.290	
					R-407C	10.010	7.750	5.840		
CO3609	MTZ64-4	5	107,71	15	R-134a	9.170	7.020	5.240	3.780	1.538,26
					R-404A	14.540	11.690	9.240	7.160	
					R-407C	12.990	10.100	7.660		
CO3610	MTZ80-4	6 1/2	135,78	18	R-134a	12.130	9.480	7.250	5.380	1.995,83
					R-404A	18.390	14.910	11.890	9.280	
					R-407C	16.600	13.110	10.100		
CO3611	MTZ100-4	8	171,26	22	R-134a	13.780	10.630	8.020	5.880	2.708,50
					R-404A	22.100	17.800	14.100	10.900	
					R-407C	20.300	15.700	11.900		
CO3612	MTZ125-4	10	215,44	27	R-134a	16.940	13.080	9.840	7.150	3.065,92
					R-404A	28.600	22.900	18.100	14.000	
					R-407C	26.900	21.300	16.500		
CO3614	MTZ160-4	13	271,55	36	R-134a	23.140	18.230	14.120	10.720	3.609,17
					R-404A	36.100	29.200	23.300	18.300	
					R-407C	34.200	27.400	21.600		

Los precios son SIN CONEXIONES (válvulas o codos soldar, opcionales).

Gama de T<sup>º</sup>: R-134a= -15°C. +20°C.; R-404A= -25°C. +10°C.

Rendimiento: T<sup>º</sup> Condensación +55°C. Recalentamiento 11,1 K. subenfriamiento líquido 8,3 K.

## COMPRESORES HERMÉTICOS

### COMPRESORES ALTA TEMPERATURA - Trifásicos 400 V. 50 Hz. R-22

Código	Modelo	HP	Cilindrada cm <sup>3</sup>	Rendimiento W				€
				+ 5°C	0°C	-5°C	-10°C	
CO3500	MT18-4	1 1/2	30,00	3.880	3.010	2.280	1.690	822,46
CO3501	MT22-4	1 3/4	37,50	5.350	4.260	3.310	2.490	876,75
CO3502	MT28-4	2	47,20	7.220	5.920	4.750	3.730	943,63
CO3503	MT32-4	2 1/4	53,00	7.880	6.380	5.080	3.950	1.021,54
CO3504	MT36-4	3	60,70	9.090	7.500	6.070	4.800	1.094,94
CO3505	MT40-4	3 1/2	67,89	9.980	8.210	6.630	5.220	1.222,20
CO3506	MT44-4		76,22	10.810	8.650	6.820	5.300	1.307,67
CO3508	MT50-4	4	85,64	11.990	9.560	7.510	5.810	1.365,95
CO3510	MT56-4			13.510	10.980	8.760	6.830	1.464,96
CO3512	MT64-4	5	107,71	15.390	12.410	9.840	7.640	1.727,56
CO3514	MT72-4			16.720	13.610	10.890	8.520	1.888,32
CO3516	MT80-4	6 1/2	135,78	19.070	15.520	12.420	9.720	2.241,96
CO3518	MT100-4	8	171,26	23.140	18.570	14.650	11.330	2.927,50
CO3519	MT125-4	10	215,44	30.170	24.410	19.470	15.260	3.443,79
CO3520	MT144-4		241,87	34.230	27.660	22.040	17.270	3.913,98
CO3521	MT160-4	13	271,55	37.900	30.650	24.440	19.190	4.053,95



Los precios son SIN CONEXIONES (válvulas o codos soldar, opcionales según tabla).

Gama de T<sup>a</sup>: MT-18 a MT-40 de -15°C. a -10°C. MT-50 a MT-160 de +15°C- a -15°C. Con T<sup>a</sup> Condensación +55°C.

### CONEXIONES NO INCLUIDAS EN EL PRECIO DEL COMPRESOR

Modelo Compresor	Conexiones para tubos Ø			Juego de Válvulas de Servicio				€
				Modelo	Código	Código Danfoss		
MT/MTZ-18/22/28	Asp.	(1")	1/2	V06	CO3700	7703004	<b>consultar</b>	
	Comp.	(1")	3/8	V01				
MT/MTZ-32/40 LT/LTZ-22/28 NTZ-48/68	Asp.	(1 1/4")	5/8	V09	CO3701	7703005		
	Comp.	(1")	1/2	V06				
MT/MTZ-44/72 LT/LTZ-40/44 NTZ-96/108	Asp.	(1 3/4")	7/8	V07	CO3702	7703006		
	Comp.	(1 1/4")	3/4	V04				
MT/MTZ-80/160 LT/LTZ-50/100 NTZ-136/215/275 SM/SZ-84/125	Asp.	(1 3/4")	7/8	V02	CO3704	7703009		
	Comp.	(1 1/4")	3/4	V04				
SM/SZ-160/175/185	Asp.	(2 1/4")	1 3/8	V08	CO3703	7703010		
	Comp.	(1 3/4")	7/8	V07				
MT/MTZ/LTZ/NTZ	Resistencia Cáter PTC 35W (Inc. pasta conductora)				CO3730	7773001		

### ACEITES

Código	Tipo de Aceite	Aplicación	Envase litros	Código Danfoss	€
CO3712	160P	MT ó LT ó SH (R-22/R-12/R-502)	1	7754001	<b>consultar</b>
CO3713			2	7754002	
CO3710	160PZ	MTZ (R-404A/R-507/R-134a/R-407C)	1	7754019	
CO3711			2	7754020	
CO3716	160Z	LTZ ó NTZ (R-404A/R-507)	2	7754026	

