



**UNIDADES CONDENSADORAS**

**ALTA/BAJA TEMPERATURA - monofásicas 220/240 V. 50 Hz.**

**R-134a**

Modelo	HP	Cil. cm <sup>3</sup>	Int. A.	Conex.		Rendimientos (Wattios) <sup>(1)</sup>				Calderín		Capilar	
				Asp	Liq	0°C	-5°C	-10°C	-25°C	Cód.	€	Cód.	€
TL4G	1/10	3,86	0,50	3/8"	1/4"	270	220	180	90	UC0360	469	UC0363	375
TL5G	1/8	5,50	0,56			320	260	220	110	UC0366	472	UC0369	378
FR6G	1/6	6,24	0,66			440	360	290	140	UC0372	451	UC0375	357
FR7,5G	1/5	6,93	0,72			480	400	320	150	UC0378	453	UC0381	359
FR8,5G	1/4	7,95	0,82			550	460	380	190	UC0384	455	UC0387	361
FR10G	1/4	9,05	0,94			580	480	400	200	UC0390	464	UC0393	369
FR11G	1/3	11,15	1,07			740	620	510	250	UC0396	486	UC0399	394
SC12G	1/3	12,90	1,19			880	740	610	290	UC0408	530	UC0411	438
SC15G	3/8	15,00	1,47			1.050	880	730	350	UC0414	603	UC0417	512
SC18G	1/2	18,00	1,67			1.210	1.010	830	400	UC0420	629	UC0423	537
SC21G	5/8	21,00	1,90			1.410	1.190	980	470	UC0426	701	UC0429	609

(\*) Rendimientos indicados con T<sup>a</sup> ambiente de +32°C. - T<sup>a</sup> gas aspirado 20°C.

Gama de temperaturas: Modelos TL4G a TL5G de -35°C. a +15°C.

Modelos FR6G a FR10G de -35°C. a +10°C.

Modelos FR11G de -35°C. a +5°C.

Modelos SC12G a SC21G de -25°C. a +15°C.

Tipo de montaje: Obús para tubo capilar sin válvulas de servicio.

Calderín con recipiente.

**BAJA TEMPERATURA - monofásicas 220/240 V. 50 Hz.**

**R-404A / R-507A**

Modelo	HP	Cil. cm <sup>3</sup>	Int. A.	Conex.		Rendimientos (Wattios) <sup>(1)</sup>				Calderín		Capilar	
				Asp	Liq	-5°C	-10°C	-25°C	-35°C	Cód.	€	Cód.	€
TL4CL	1/5	3,86	0,74	3/8"	1/4"	380	320	180	110	UC0474	442	UC0475	348
FR6CL	1/4	6,24	1,21			540	470	270	170	UC0467	464	UC0468	369
FR8,5CL	1/4	8,50	1,53			690	600	340	210	UC0470	473	UC0471	379
SC10CL	1/3	10,30	1,70			860	730	390	220	UC0448	563	UC0447	471
SC12CL	1/2	12,90	2,18			1.090	940	550	320	UC0450	565	UC0453	473
SC15CL	3/8	15,30	2,54			1.300	1.120	650	400	UC0456	576	UC0459	499
SC18CL	5/8	18,00	2,95			1.380	1.210	750	480	UC0462	715	UC0465	623
SC21CL	3/4	21,00	3,43				1.410	840	540	UC0469	834	UC0472	709

**ALTA/MEDIA TEMPERATURA - monofásicas 220/240 V. 50 Hz.**

**R-404A / R-507A**

Modelo	HP	Cil. cm <sup>3</sup>	Int. A.	Conex.		Rendimientos (Wattios) <sup>(1)</sup>				Calderín		Capilar	
				Asp	Liq	0°C	-5°C	-10°C	-25°C	Cód.	€	Cód.	€
TL4DL	1/5	3,86	1,29	3/8"	1/4"	450	380	310	270	UC2750	460	UC2753	368
FR6DL	1/4	6,24	2,28			710	600	510	430	UC2756	477	UC2759	384
SC10DL	1/3	10,30	3,31			1.220	1.050	880	740	UC2762	573	UC2765	481
SC12DL	1/2	12,90	4,05			1.390	1.210	1.030	860	UC2768	595	UC2771	501
SC15DL	5/8	15,30	5,20			1.770	1.520	1.290	1.080	UC2774	845	UC2777	720

(\*) Rendimientos indicados según condiciones EN 13215

T<sup>a</sup> ambiente de +32°C. - T<sup>a</sup> gas aspiración 20°C. - Recalentamiento 10K.

Gama de temperaturas: -45°C. a -10 (-5)°C.

Tipo de montaje: Obús para tubo capilar sin válvulas de servicio.

Calderín con recipiente,