



**SILENCIADORES - SEPARADORES DE ACEITE - ACUMULADORES**

**Eliminan vibraciones y ruidos.**

Código	Modelo	Conexión Soldar	€
SP0050	M-2	3/8"	50,10
SP0051	M-3	1/2"	74,25
SP0052	M-5	5/8"	93,25
SP0053	M-10	7/8"	138,25
SP0054	M-15	1 1/8"	130,35
SP0055	M-20	1 3/8"	151,35
SP0056	M-30	1 5/8"	241,30
SP0057	M-60	2 1/8"	461,05
SP0058	M-80	2 5/8"	503,90
SP0059	M-110	3 1/8"	567,60



**Silenciadores Ajustables**

Código	Modelo	Conexión Soldar	€
SP0060	AM-5	5/8"	233,90
SP0061	AM-10	7/8"	246,40
SP0062	AM-25	1 1/8"	257,25

Provistos de un vástago que permite ajustar el silenciador a las características del sistema para obtener las mejores prestaciones.

Instalables tanto en horizontal como en vertical.



**Separadores de Aceite Herméticos**

Código	Modelo	Conexión Soldar	€
SP0001	W-55824	1/2"	231,70
SP0002	W-55855	5/8"	242,10
SP0003	W-55877	7/8"	268,85
SP0004	W-55889	1 1/8"	279,75
SP0005	W-55901	1 3/8"	303,05



**Separadores de Aceite Desmontables**

Código	Modelo	Conexión Soldar	€
SP0010	F-58824	1/2"	419,70
SP0011	F-58855	5/8"	348,65
SP0012	F-58877	7/8"	356,60
SP0013	F-58889	1 1/8"	395,10
SP0014	F-58901	1 3/8"	410,90
SP0015	F-58921	1 5/8"	443,65

Modelos	R-12				R-22			
	-40°C		4°C		-40°C		4°C	
	Kcal./h	HP	Kcal./h	HP	Kcal./h	HP	Kcal./h	HP
F-58824-W55824	3.024	4,71	4.536	7,06	4.536	7,0	6.048	9,4
F-58855-W22855	9.072	14,13	12.096	18,84	13.608	21,20	16.632	25,9
F-58877-W55877	13.608	21,19	16.632	25,91	21.168	32,90	24.192	37,68
F-58889-W55889	18.144	28,26	22.680	35,33	27.216	42,39	31.752	49,46
F-58901-W55901	22.680	35,33	30.240	47,10	34.776	54,16	40.824	63,59
F-58921	27.216	42,39	34.776	54,16	42.336	65,90	52.920	82,40

Modelos	R-502				R-134a			
	-40°C		4°C		-40°C		4°C	
	Kcal./h	HP	Kcal./h	HP	Kcal./h	HP	Kcal./h	HP
F-58824-W55824	4.536	7,0	6.048	9,40	3.024	4,71	5.141	8,00
F-58855-W22855	14.231	22,0	17.237	26,80	9.677	15,07	13.608	21,20
F-58877-W55877	22.680	35,3	25.704	40,00	4.213	22,14	19.354	29,68
F-58889-W55889	28.728	44,7	34.776	54,17	19.354	29,68	25.704	40,00
F-58901-W55901	36.288	56,5	43.848	68,30	24.192	37,70	34.776	54,16
F-58921	48.384	75,3	52.920	82,40	28.728	44,70	40.210	62,13



**Acumuladores**

Código	Modelo	Conex.	Ø	Longitud Tubo	€
SP0020	AS384	1/2"	3	8	60,65
SP0021	AS3105	5/8"	3	10	68,10
SP0022	AS3125	5/8"	3	12	68,10
SP0023	AS3126	3/4"	3	12	73,85
SP0024	AS3145	5/8"	3	14	81,35
SP0025	AS3146	3/4"	3	14	86,55
SP0026	AS464	1/2"	4	6	99,55
SP0027	AS465	5/8"	4	6	99,55
SP0028	AS4105	5/8"	4	10	103,25
SP0029	AS4106	3/4"	4	10	104,55
SP0030	AS597	7/8"	5	9	127,65
SP0032	AS5126	3/4"	5	12	135,45

Código	Modelo	Conex.	Ø	Longitud Tubo	€
SP0033	AS5127	7/8"	5	12	140,15
SP0034	AS5137	7/8"	5	13	145,70
SP0035	AS5139	1 1/8"	5	13	149,40
SP0036	AS5179	1 1/8"	5	17	158,85
SP0037	AS1711	1 3/8"	5	17	180,75
SP0038	AS6117	7/8"	6	11	195,40
SP0039	AS6139	1 1/8"	6	13	202,50
SP0040	AS6141	1 3/8"	6	14	214,65
SP0041	AS61713	1 5/8"	6	17	217,25
SP0042	AS62013	1 5/8"	6	20	259,50
SP0043	AS62513	1 5/8"	6	25	316,25

Presenta conexiones de cobre sólido para fácil instalación en aplicaciones de líneas de succión. Amplio rango de tamaños.